

V-TUF JETWASH HOSE SPEC SHEET



	MAX WORKING PRESSURE (BAR)	MINIMUM BURST PRESSURE (BAR)	TEMPERATURE RANGE	BORE - ID(MAX) Ø	DIAMETER OD Ø	MINIMUM BEND RADIUS (mm)	WEIGHT (GRAMS PER METER)	APPLICATION	INNER TUBE	REINFORCEMENT	OUTER COVER
1/4 1 Wire	320	1120	-40 oC to 155 oC	1/4" 6.4mm	13.5	100	228	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
1/4 2 Wire	420	1650	-40 oC to 155 oC	1/4" 6.4mm	14.9	100	386	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Twin Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
5/16 1 Wire	320	960	-40 oC to 155 oC	5/16" 8mm	15.5	115	265	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
5/16 2 Wire	420	1650	-40 oC to 155 oC	5/16" 8mm	16.9	115	427	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Twin Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
3/8 1 Wire	250	820	-40 oC to 155 oC	3/8" 9.5mm	17.4	125	343	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
3/8 2 Wire	415	1600	-40 oC to 155 oC	3/8" 9.5mm	18.3	130	559	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Twin Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
1/2 1 Wire	200	750	-40 oC to 155 oC	1/2" 12.7mm	20.5	180	420	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber
1/2 2 Wire	320	1250	-40 oC to 155 oC	1/2" 12.7mm	22	180	651	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Twin Braid	Oil, Abrasion Ozone and weather pin pricked synthetic rubber

SWAGE DIMENSIONS	¼	5/16	3/8	1/2
1SN	17mm	17.5mm	20mm	22.5mm
2SN	17.5mm	18mm	21.5mm	24mm