

tufSCRUB T

EFFICIENT AND SUSTAINABLE



The V-TUF tufSCRUB-T features key upgrades, primarily in the upper section. A new tubular AISI 304 stainless steel handle (32 mm diameter) replaces the old rotational handle, paired with an integrated dashboard featuring a double shell and single brush grip for better maneuverability. A 5-liter recovery tank clips onto the handle for easy removal and cleaning.

The filter system includes a steel mesh cage with float balls to block the suction pipe when water reaches maximum levels. The lower components, including the reliable brush and suction motors, remain unchanged.

The updated design lowers the center of gravity for improved ergonomics and ease of use. The suction pipe now connects directly to the tank, removing the need for a gasket and hook. With unchanged motors, parts, and accessories, the tufSCRUB-T maintains compatibility with existing stocks.



TECHNICAL FEATURES

BATTERY SPEC	36V - 13Ah
WORKING WIDTH	410mm
WORKING CAPACITY (SQM PER HOURS)	500
POWERED: B BATTERY	B 36 VOLT / 13 ah
BRUSH SIZE: NB X mm	2/205
SPECIFIC BRUSH PRESSURE (gr/cm ²)	145/175/210
Rpm BRUSH MOTOR	gr/cm 40
WAC WATER COLUMN (mm h ₂ o)	900 mmh 20
CLEAR WATER TANK CAPACITY	3 l
DIRTY WATER TANK CAPACITY	5 lt
BATTERY CAPACITY (60 to 90 minutes)	1 h
WEIGHT INCLUDING BATTERIES	37kg (1 battery) 40kg (2 batteries)
RPM OF THE BRUSHES	140-175-220 rpm
DIMENSIONS (WxDxH)	490x1250x510mm



LIGHT CLEANING



INTERMEDIATE CLEANING



ENERGY CLEANING



FINISHING AND POLISHING



SPRAY SHINING



POLISHING



PAD DRIVER



PPL STANDARD



TYNEX IN CARBON



PES BRISTLES MIXTURE



MOQUETTE

WIDE RANGE OF PAD AND BRUSHES