



Non-Caustic Wash & Wax

Safety Data Sheet

according to 1907/2006/EC, Article 31


SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	Wash & Wax Traffic Film Remover (TFR with Shine)
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.
1.3. Details of the supplier of the safety data sheet	
Company	V-TUF is a brand of Fenco Group Ltd
Address	Fenco Group Ltd Crofton Drive Allenby Industrial Estate Lincoln LN3 4NR United Kingdom
Website	www.V-TUF.com
Tel	01522 515767
Fax	01522 787838
Email	enquiries@v-tuf.com
1.4. Emergency telephone number	
Emergency telephone number	01522 515767
Company	V-TUF Helpline - Opening Hours: 7am – 5pm - Monday ~ Friday

© Copyright V-TUF 2017

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. V-TUF and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.1. Classification - 1999/45/EC	Xi; R36 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Dam. 1: H318;
2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention.



	P337+P313 - If eye irritation persists: Get medical advice/attention. P363 - Wash contaminated clothing before reuse.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to REQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures							
67/548/EEC / 1999/45/EC							
Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. Cat. 3; R40 Xn; R22 Xi; R36	
Ethylene glycol monobutyl ether (2-Butoxyethanol)	603-014-00-0	111-76-2	203-905-0		0 - 0.5%	Xn; R20/21/22 Xi; R36/38	
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37	1 - 10%	C; R34	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	C; R35	
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3		0 - 0.5%	Xn; R22	

© Copyright V-TUF 2017

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. V-TUF and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.



EC 1272/2008						
Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
COCONUT DIETHANOLMINE		8051-30-7			0.5 - 1%	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 2: H411;
WATER					80 - 90%	
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319;
D-Glucopyranose, Oligomeric, Decyl, Octyl, Glycoside					0 - 0.5%	Eye Dam. 1: H318
1-Propanaminium, 3 Amino-N(carboxymethyl)N,N-Dimethyl N Coco acyl dervis inner salts					0 - 0.5%	Skin Irrit. 2: H315
Ethylene glycol monobutyl ether (2-Butoxyethanol)	603-014-00-0	111-76-2	203-905-0		0 - 0.5%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315
2,2'-Iminodiethanol	603-071-00-1	111-42-2	203-868-0		0 - 0.5%	Acute Tox. 4: H302; STOT RE 2: H373; Skin Irrit. 2
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37	1 - 10%	Met. Corr. 1: H290; Skin Corr. 1B: H314; Eye Dam. 1: H318
COCAMIDOPROPYL BETAINE			931-296-8		0.5 - 1%	Eye Dam. 1: H318; Aquatic Chronic 3: H412;
ALCOHOL ETHOXYLATE		6843-9-46-3			0.5 - 1%	Acute Tox. 4: H302; Eye Dam. 1: H318;
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	0.5 - 1%	Eye Irrit. 2: H319
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	Skin Corr. 1A: H314;
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3		0 - 0.5%	Acute Tox. 4: H302;

© Copyright V-TUF 2017

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. V-TUF and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.



SECTION 4: First aid measures

4.1. Description of first aid measures	
Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media	Carbon dioxide (CO ₂).
5.2. Special hazards arising from the substance or mixture	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	Wear suitable respiratory equipment when necessary.



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
	Wear suitable protective equipment. Adopt best Manual Handling considerations when handling, carrying and dispensing.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for containment and cleaning up	
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage, including any incompatibilities	
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.



SECTION 8: Exposure controls/personal protection

8.1. Control parameters									
8.1.1. Exposure Limit Values									
Ethylene glycol monobutyl ether (2-Butoxyethanol)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">WEL 8-hr limit ppm: 25</td> <td style="width: 50%;">WEL 8-hr limit mg/m3: 123</td> </tr> <tr> <td>WEL 15 min limit ppm: 50</td> <td>WEL 15 min limit mg/m3: 101.2</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total inhalable dust:</td> <td>WEL 15 min limit mg/m3 total inhalable dust:</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total respirable dust:</td> <td>WEL 15 min limit mg/m3 total respirable dust:</td> </tr> </table>	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2	WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:	WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123								
WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2								
WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:								
WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:								
Mono ethylene glycol (Ethane-1,2-diol particulate)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">WEL 8-hr limit ppm: -</td> <td style="width: 50%;">WEL 8-hr limit mg/m3: 10</td> </tr> <tr> <td>WEL 15 min limit ppm: -</td> <td>WEL 15 min limit mg/m3:</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total inhalable dust:</td> <td>WEL 15 min limit mg/m3 total inhalable dust:</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total respirable dust:</td> <td>WEL 15 min limit mg/m3 total respirable dust:</td> </tr> </table>	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3:	WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:	WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10								
WEL 15 min limit ppm: -	WEL 15 min limit mg/m3:								
WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:								
WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:								
Mono ethylene glycol (Ethane-1,2-diol vapour)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">WEL 8-hr limit ppm: 20</td> <td style="width: 50%;">WEL 8-hr limit mg/m3: 52</td> </tr> <tr> <td>WEL 15 min limit ppm: 40</td> <td>WEL 15 min limit mg/m3: 104</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total inhalable dust:</td> <td>WEL 15 min limit mg/m3 total inhalable dust:</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total respirable dust:</td> <td>WEL 15 min limit mg/m3 total respirable dust:</td> </tr> </table>	WEL 8-hr limit ppm: 20	WEL 8-hr limit mg/m3: 52	WEL 15 min limit ppm: 40	WEL 15 min limit mg/m3: 104	WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:	WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
WEL 8-hr limit ppm: 20	WEL 8-hr limit mg/m3: 52								
WEL 15 min limit ppm: 40	WEL 15 min limit mg/m3: 104								
WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:								
WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:								
Sodium hydroxide	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">WEL 8-hr limit ppm: -</td> <td style="width: 50%;">WEL 8-hr limit mg/m3: -</td> </tr> <tr> <td>WEL 15 min limit ppm: -</td> <td>WEL 15 min limit mg/m3: 2</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total inhalable dust:</td> <td>WEL 15 min limit mg/m3 total inhalable dust:</td> </tr> <tr> <td>WEL 8-hr limit mg/m3 total respirable dust:</td> <td>WEL 15 min limit mg/m3 total respirable dust:</td> </tr> </table>	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2	WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:	WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -								
WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2								
WEL 8-hr limit mg/m3 total inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:								
WEL 8-hr limit mg/m3 total respirable dust:	WEL 15 min limit mg/m3 total respirable dust:								
DNEL: Derived no-effect level.									
No data is available on this product.									
8.2. Exposure controls									
8.2.1. Appropriate engineering controls	Not normally required								
8.2.2. Individual protection measures	Wear suitable protective clothing.								
Eye / face protection	Approved safety goggles.								
Skin protection - Handprotection	Chemical resistant gloves (PVC).								
Respiratory Protection	Not normally required.								



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties	
Appearance	Aqueous solution
Colour	Various
Odour	Mild
pH	12
Relative density	1.02 - 1.06
Solubility	Soluble in water

SECTION 10: Stability and Reactivity

10.2. Chemical stability	
	Stable under normal conditions.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects	
Skin corrosion/irritation	Causes severe inflammation and may damage the cornea. Irritating to eyes and skin.

SECTION 12: Ecological information

12.1. Toxicity	
COCAMIDOPROPYL BETAINE	Daphnia EC50/48h: 21.5000 mg/l Algae IC50/72h: 30.0000 mg/l
12.2. Persistence and degradability	
	DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts. More than 90% Biodegradable.
12.3. Bio accumulative potential	
	Does not bio accumulate.

© Copyright V-TUF 2017

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. V-TUF and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.



SECTION 13: Disposal considerations

General information	
	Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for user	
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.2. Chemical safety assessment	
	No chemical Safety assessment has been carried out by the supplier.



SECTION 16: Other information

Other information	
Text of risk phrases in Section 3	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R22 - Harmful if swallowed. R34 - Causes burns. R35 - Causes severe burns. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes. R40 - Limited evidence of a carcinogenic effect.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Eye Dam. 1: H318 - Causes serious eye damage. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Acute Tox. 4: H302 - Harmful if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Carc. 2: H351 - Suspected of causing cancer . Acute Tox. 4: H312 - Harmful in contact with skin. Acute Tox. 4: H332 - Harmful if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Met. Corr. 1: H290 - May be corrosive to metals. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Further Information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.